



„The exclusive POS System

Specifications – P2100

- Structure d'écran robuste avec écran tactile résistif ou capacitif
- Sans ventilateur: silencieux et fiable
- Professionnel de l'hôtellerie avec protection de l'écran IP64
- Processeur Intel Celeron 2,0 GHz, jusqu'à 8 Go de RAM

P2100		
System	CPU	Intel Celeron J1900, Quad-Core, 2.0 GHz (fanless) 4 GB DDR3 RAM (up to 8 GB)
	System memory	BayTrail platform
	Chipset	CFast card support
	Compact Flash	320 GB HDD, optional SSD
	Hard disk drive	On-board
	Audio	WS7E / POSReady 7 / Windows
	Supported operating systems	Embedded 8.1 Industry / Windows 10 / Linux Aluminium
	Housing	Intel HD Graphics
Display	Graphics chip	38.1 cm (15")
	LCD screen size	1024 x 768 pixels
	Maximum resolution	350 cd/m²
	Brightness	5-wire resistive, Projected Capacitive (optional) 3x USB 2.0; 1x USB 3.0
	Touch screen	3x DB9, 1x RJ45
Interfaces	USB	Available on demand
	Serial/COM	1x RJ45 10/100/1000 Base-T
	Parallel	1x
	LAN	1x
	VGA	1x RJ11 (12 V)
	PS/2	Line-out, mic-in, speaker
	Cash drawer port	
	Audio	
PSU	Power adapter	90 watts
Other	Dimensions (WxDxH)	323.6 x 264.2 x 368 mm
	Weight	7.6 kg
	Operating temperature	0 to 40 °C
	Certification	CE, FCC, RoHS, IP64 (front panel)
	Mount	VESA 100 mm
Options	Magnetic stripe reader	Choice of MSR (track 1, 2, 3), MSR + iButton reader, MSR + smart card reader + iButton reader, MSR + smart card reader + fingerprint reader
	Customer display	VFD, 2 x 20 characters (integrated or pole type)
	Customer-facing screen	20.3 cm (8") or 38.1 cm (15") screen size
	Barcode scanner	1D or 2D barcode scanner (optional RFID capability)
	Waiter lock	iButton (optional RFID capability), Addimat (RS232)
	RFID	13.56 MHz (MIFARE), 125KHz
	Colour	Black, white
	UPS	Up to 1 hour battery backup

